

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

DESIGNED FOR USE WITH
.085 DIA S.R. CABLE
CABLE ENTRY DIAMETER
MINIMUM

CONTACT

.021

HOUSING

.089

LOC

AJ

DIST

00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	B	REV PER ECO 07-004710	3/14/2007	DW	KW

REF PLANE

.320
(8.1mm)

REF

OSM PLUG

.120
(3.0mm)

DIA

.312 HEX
(7.9 mm)

±.020

.437
(11.1mm)

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A	TEMPERATURE RATING -65°C TO +105°C
Frequency Range (GHz) DC to 18.0	Fig. 310.1	Vibration MIL-STD-202, Method
Volt Rating (VRMS MAX)	Recommended Mating	204, Condition D
@ Sea Level 335	Torque 7 to 10 In-LBs	Shock MIL-STD-202, Method 213,
VSWR 1.05 + .005f(GHz)	Mating Characteristics:	Condition I
Insertion Loss (dB MAX) .03 √f(GHz)	Insertion (MAX Lbs) N/A	Thermal Shock MIL-STD-202,
RF Leakage (dB MIN) -[90-f(GHz)]	Withdrawal (MIN Oz) N/A	Method 107, Condition B,
Corona, 70,000 Ft (VRMS MIN) 250	Force to Engage and	EXCEPT HIGH TEMP 115°C
Dielectric Withstanding Voltage	Disengage (In-Lbs MAX) 2.0	Moisture Resistance MIL-STD-202,
(VRMS MIN) @ Sea Level 1000	Center Contact Captivation	Method 106
Contact Resistance (Milliohms MAX)	Axial (Lbs) N/A	Corrosion - MIL-STD-202, Method
Center Contact 3.0	Radial (In-Oz) N/A	101, Condition B, 5% salt spray
Outer Contact 2.0	Cable Retention	
Cable to Housing 0.5	Axial Force (Lbs) 30	
RF High Potential @ Sea Level	Torque (In-Oz) 16	
(VRMS MIN @ 5 MHz) 670	Weight (Grams) T.B.D.	
I.R.(Megohms MIN) 10,000		

COMPONENT	MATERIAL	FINISH
HOUSING COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H OR BRASS PER ASTM-B-16	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
RETAINING RING	BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
INCHES

MATERIAL -

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± .005
4 PLC ± -
ANGLES ± 1°
FINISH -

DWN JPD 9/1/76
CHK RMF 9/9/76
APVD RMF 9/13/76
PRODUCT SPEC -
APPLICATION SPEC -
WEIGHT -

tyco
Electronics

Tyco Electronics Corporation
Harrisburg, PA 17105-3608

NAME OSM STRAIGHT CABLE PLUG
DIRECT SOLDER ATTACHMENT -

SIZE A2
CAGE CODE 00779
DRAWING NO C-1050547
RESTRICTED TO -

CUSTOMER DRAWING

SCALE 5:1
SHEET 1 of 1
REV B

1050547-1

PART NUMBER

1050547

AMP 1471-9 REV 31MAR2000

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2001-5032-00](#)